Name

reference tests –

how to markup

link adr in .UR .UE or simply in parantheses

- man and mandoc convert UR/UE to **<** and **>**.
- pandoc transforms

```
See the `Python home page <https://www.python.org>`_ for info.
```

  to

```
see See the Python home page (https://www.python.org) for info.
```

test for references in man pages

embedded in a paragraph

- at line start
- in line
- at eol

at start of paragraph

- followed by text
- at eol

at end of paragraph

tests

See <https://docutils.sourceforge.io/docs/user/rst/quickref.html#explicit−markup> for more

See the Python home page <https://www.python.org>
for info.

External hyperlinks, like Python <https://www.python.org> .

Want to learn about my favorite programming language <https://www.python.org> ?

Clicking on this internal hyperlink will take us to the target below.

The hyperlink target above points to this paragraph.

- bullet list
- second item, with hyperlink target.

See the Python <https://www.python.org>
home page for info.

Write to me <mailto:jdoe@example.com>
with your questions.

The one−liner <https://docutils.sourceforge.io/rst.html>
and starts−on−this−line <https://docutils.sourceforge.net/rst.html>
or entirely−below <https://docutils.sourceforge.net/rst.html>
point to <https://docutils.sourceforge.io/rst.html> and in man are ... ?

reference tests()

Escaped whitespace is preserved as intentional spaces, e.g.:

some reference <../local path with spaces.html>
to a local path.

Anonymous hyperlink references are specified with two underscores instead of one:

See the web site of my favorite programming language <https://www.python.org> .

Anonymous targets begin with ".. __:"; no reference name is required or allowed: